# XR10910



16:1 Sensor Interface AFE

### **General Description**

The XR10910 is a unique sensor interface integrated circuit with an on-board 16:1 multiplexer, offset correction DAC, instrumentation amplifier and voltage reference. The XR10910 is designed to integrate multiple bridge sensors with a microcontroller (MCU) or field-programmable gate array (FPGA).

The integrated offset correction DAC provides digital calibration of the variable and in many cases substantial offset voltage generated by the bridge sensors. The DAC is controlled by an I2C compatible 2 wire serial interface. The serial interface also provides the user with easy controls to the XR10910's many functions such as input and gain selection.

An integrated LDO provides a regulated voltage to power the input bridge sensors and is selectable, between 3V and 2.65V, via the serial interface for lower voltage compatibility. The LDO current can be sensed and a proportional voltage present at the output of the IC for monitoring the LDO current.

The XR10910 offers 8 fixed gain settings (from 2V/V to 760V/V), each with an error of only  $\pm 0.5\%$ , that are selectable via the I2C interface. It also offers less than 1mV maximum input offset voltage, 100pA maximum input bias current, and 100pA maximum input offset current.

The XR10910 is designed to operate from 2.7V to 5V supplies and is specified over the industrial temperature range of -40°C to +85°C. Of is offered in a space saving 6mm x 6mm QFN-40 package. It consumes less than 556µA maximum supply current and offers a sleep mode for added power savings.

The low power, low input bias current and integrated features make the XR10910 well suited for both industrial and consumer applications using bridge sensors.

# **Typical Application**



#### FEATURES

- Integrated features for interfacing multiple bridge sensors with an MCU or FPGA:
   16:1 differential mux with l<sup>2</sup>C interface

  - Instrumentation amplifier
  - 🗆 LDO
  - Offset correction DAC with I<sup>2</sup>C interface (±560mV offset correction range - RTI)
- Eight selectable voltage gains from 2V/V
- to 760V/V with only  $\pm 0.5\%$  gain error
- 1mV maximum input offset voltage
- 00pA maximum input bias current 556µA maximum supply current
- 2.7V to 5V analog supply voltage range
- 1.8V to 5V digital supply voltage range
- 1.8V to 5V digital supply voltage range
  -40°C to +85°C temperature range
- 6mm x 6mm QFN-40 package

#### APPLICATIONS

- Bridge sensor interface
- Pressure & temperature sensors
- Strain gauge amplifier
- Industrial process controls
- Weigh scales

Ordering Information - back page



Figure 2. 0.1Hz to 10Hz RTI Voltage Noise

# **Absolute Maximum Ratings**

Stresses beyond the limits listed below may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

Analog Supply Voltage (V <sub>CC)</sub>	0V to 5.5V
Digital Supply Voltage (V <sub>DD</sub> )	0V to 5.5V
Digital Input/Output (V <sub>DDIO</sub> )	0V to 5.5V
V <sub>IN</sub>	0 to $V_{CC}$
Differential Input Voltage (current limit of 10mA)	V <sub>CC</sub>
ESD Rating (HBM - Human Body Model)	4kV

### **Operating Conditions**

Analog Supply Voltage Range	2.7V to 5.25V
Digital Supply Voltage Range	1.7V to 5.25V
Operating Temperature Range	40°C to 85°C
Junction Temperature	150°C
Storage Temperature Range	65°C to 150°C
Lead Temperature (Soldering, 10s)	260°C
Package thermal resistance $\theta_{JA}$	32°C/W

NOTE:

1. JEDEC standard, multi-layer test boards, still air.

uti-tare and the and t



# **Electrical Characteristics**

 $T_A$  = 25°C,  $V_{CC}$  = 3.3V,  $V_{DD}$  = 1.8V,  $R_L$  = 10k $\Omega$  to 1.5V; G = 760; unless otherwise noted.

Symbol	Parameter	Conditions	Min	Тур	Max	Units
DC Perform	ance	•				
V <sub>IO</sub>	Input offset voltage	Input referred	-1	±0.02	1	mV
d <sub>VIO</sub>	Input offset voltage average drift			3		μV/°C
IB	Input bias current		-100	15	100	pА
I <sub>OS</sub>	Input offset current		-100	1	100	pА
PSRR	Power supply rejection ratio	V <sub>CC</sub> = 2.7V to 5V	60	91		dB
	Gain = 2			2.0		V/V
	Gain = 20			20.0		V/V
	Gain = 40			40.0		V/V
Onin	Gain = 80			80.0		V/V
Gain	Gain = 150	- Nominal; refer to Gain Register Table (pg. to)		150.0		V/V
	Gain = 300	<u></u>		299.9		V/V
	Gain = 600	ne nu.		599.6		V/V
	Gain = 760			759.4		V/V
G <sub>E</sub>	Gain error		-0.5		0.5	%
	Gain error vs temperature	nº ino		±10		ppm/°C
Isvcc	V <sub>CC</sub> supply current	No load to output; no load to LDO		435	530	μA
ISVCCD	Disable V <sub>CC</sub> supply current	No load to output; no load to LDO		48	59	μA
I <sub>SVDD</sub>	V <sub>DD</sub> supply current	No load to output, no load to LDO; I2C running		22	26	μA
ISTOTAL	Total supply current	No load to output; no load to LDO		457	556	μA
	Tatal dia dala anna barana di	No load to output; no load to LDO; LDO DIS		45		μA
SDTOTAL		No load to output; no load to LDO; LDO EN		70	85	μA
Input Chara	cteristics	40 0 O				
	Input impedance	8, 70_		1013    11.2		ΩllpF
CMIR	Common mode input range	1 ROL	0.5	0.23 to 3.06	2.5	v
CMRR	Common mode rejection ratio	Input referred. $V_{CM} = 0.5$ to 2.0V	75	88		dB
Output Cha	racteristics	-	T	1		
V <sub>OUT</sub>	Output voltage swing	$R_L = 10 k\Omega$ to 1.5V	0.1	0.04 to 3.29	3.1	v
V <sub>OO</sub>	Output offset	Offset DAC 0 00 0000 0000; G = 2	1.4	1.5	1.6	V
Offset DAC	1	1	1	1		1
	Offset DAC range	RTI (referred to input)	±560			mV
	Offset monotonicity		8	10		Bits
LDO	1	1	1	1		1
	Output voltage	1.5k load, LDO bit LOW	-6%	3	+6%	V
		1.5k load, LDO bit HIGH	-6%	2.65	+6%	V
	Dropout voltage	V <sub>CC</sub> = 2.8V, LDO = 2.65V, I <sub>LOAD</sub> = 10mA			150	mV
	Output current		10	25		mA
	Power supply rejection ratio	Output referred, $V_{CC} = 3V$ to 5V, LDO = 2.65V	45	63		dB
		Output referred, $V_{CC} = 3.3V \text{ to5V}$ , LDO = 3V	45	63		dB
	Output current sense transimpedance slope	Output voltage relative to $1.5V / LDO$ current, $G = 2$	0.08	0.1	0.12	V/mA
	Output current sense range clip	G = 2		18.8		mA



### **Electrical Characteristics (Continued)**

 $T_A$  = 25°C,  $V_{CC}$  = 3.3V,  $V_{DD}$  = 1.8V,  $R_L$  = 10k $\Omega$  to 1.5V; G = 760; unless otherwise noted.

Max Units	Тур	Min	Conditions	ol Parameter							
			Dynamic Performance								
kHz	66		G = 760	2dP bandwidth	DW/						
kHz	1300		G = 2		DVV						
V/µs	1		$V_{OUT} = 1V_{pp}$ ; Gain = 2	Slew rate	SR						
nV/√Hz	75		f = 10Hz								
nV/√Hz	46		f = 100Hz	Input voltage noise - RTI	e <sub>ni</sub>						
nV/√Hz	35		f = 1kHz								
fA/√Hz	0.6		f = 10Hz	Input current noise	i <sub>n</sub>						
μV <sub>pp</sub>	2		f = 0.1 to 10Hz	Peak-to-peak noise	e <sub>npp</sub>						
dB	90		Channel-to-channel, f = 1kHz	Crosstalk	XTALK						
μs	3.5		Analog ready after serial register finished write	Set-up time, 1% settling	T <sub>S</sub>						
μs	9.6		Wake from ACK of SLEEP_OUT command	Wake up time, 1% settling	T <sub>WAKE</sub>						
	2 90 3.5 9.6		f = 0.1 to 10Hz Channel-to-channel, f = 1kHz Analog ready after serial register finished write Wake from ACK of SLEEP_OUT command	Peak-to-peak noise      Crosstalk      Set-up time, 1% settling      Wake up time, 1% settling	e <sub>npp</sub> XTALK T <sub>S</sub> T <sub>WAKE</sub>						

# **Digital Characteristics (CMOS)**

Digital C	Characteristics (CMOS)	ntionecanult				
Symbol	Parameter	Conditions	Min	Тур	Max	Units
V <sub>IH</sub>	Logic Input HIGH	a set of	$0.7 \times V_{DD}$		V <sub>DD</sub>	V
V <sub>IL</sub>	Logic Input LOW		0		$0.3 \times V_{DD}$	V
I <sub>IH</sub>	Input Leakage HIGH	V <sub>1</sub> = V			10	μA
IIL	Input Leakage LOW	V <sub>I</sub> = 0	-10			μA
CLK <sub>F</sub>	Clock Rate	8° 1° 8°			0.4	MHz

# I<sup>2</sup>C Bus Timing

```
T_A = -40 to +85^{\circ}C, V_{DD} = 1.8 - 5V; unless otherwise noted.
```

Symbol	Parameter Parameter	Standa I²C-	rd Mode BUS	Fast I²C-	Units	
		Min	Max	Min	Max	
f <sub>SCL</sub>	Operating frequency	0	100	0	400	kHz
T <sub>BUF</sub>	Bus free time between STOP and START	4.7		1.3		μs
T <sub>HD;STA</sub>	START condition hold time	4.0		0.6		μs
T <sub>SU;STA</sub>	START condition setup time	4.7		0.6		μs
T <sub>HD;DAT</sub>	Data hold time	0		0		μs
T <sub>VD;ACK</sub>	Data valid acknowledge		0.6		0.6	μs
T <sub>VD;DAT</sub>	SCL LOW to data out valid		0.6		0.6	ns
T <sub>SU;DAT</sub>	Data setup time	250		150		ns
T <sub>LOW</sub>	Clock LOW period	4.7		1.3		μs
T <sub>HIGH</sub>	Clock HIGH period	4.0		0.6		μs
T <sub>F</sub>	Clock/data fall time		300		300	ns
T <sub>R</sub>	Clock/data rise time		1000		300	ns
T <sub>SP</sub>	Pulse width of spikes tolerance	0.5		0.5		μs



# **Electrical Characteristics (Continued)**





### **Register Information**

Table 1. Register List

Reg No.		Namo	Function	R/	Byte of	Paramotor	Default	Power-up	Remark			
Hex	Dec	Name	Tunction	C	Parameter	Falanletei	Code	Condition	Hemark			
0x00	0	NOP	No operation	с	0		N/A		Does not execute a function. NOP is used to test successful I <sup>2</sup> C communication			
Reset												
0x01	1	SW_RESET	Software reset	С	0		N/A		Resets all registers to default values			
Read ID												
0x02	2	DEVICE_ID	Read Device ID	R	2	[15:0]: report "0910" in BCD	0x0910	2	Instructs the XR10910 to report its device ID "0910" in binary form (0000 1001 0001 0000)			
0x03	3	VERSION_ID	Read HW & SW version numbers	R	2	[15:12]: reserved [11:8]: Hardware version # [7:0]: Software version #	N/A	Jrec	Initial H/W version number is '0'; Initial S/W version number is '01'.			
Slee	p in/ou	t				λ	62					
0x04	4	SLEEP_OUT _ REG	Normal operating mode, system active	с	0	ionez	N/A	Active	Puts the XR10190 into active mode. (wake up)			
0x05	5	SLEEP_IN_ REG	Sleep Mode	С	0	ts per B	N/A	Active	Puts the analog portion of the XR10910 into sleep mode. During sleep mode, the only I <sup>2</sup> C command that can be received/processed is the SLEEP_OUT command (0x04). All other register addresses will be ignored.			
Basi	c Confi	g										
0x06	6	Gain	Gain select	R/W	1	[2:0]: Gain select	0x00	Gain = 2	Eight gain settings are selectable (from 2V/V to 760V/V), refer to the Gain Register Table for more information.			
0x07	7	LDO	LDO Settings	R/W	ol e f	[0]:LDO 3V, 2.65V [1]:LDO disable	0x00	LDO = 3V	Bit 0 controls the LDO voltage (0: 3V; 1: 2.65V). Bit 1 (Sleep Mode only). Bit 1 controls whether the LDO shuts down or stays on during Sleep Mode. (0: Enable; 1: Disable). When the XR10910 is active, the LDO is always on.			
0x08 8		LDO Current Sense Select	LDO Current Sense	eg le	200		N/A	Off	When on, the LDO current is sensed and a proportional voltage is present at the output of the XR10910. Current Sense Mode remains active until an input select command is received by the XR10910.			
			<u> </u>	no					·			

# XR10910

Reg No.		N		R/	Byte of	<b>.</b> .	Default	Power-up	Demode	
Hex	Dec	Name	Function	C	Parameter	Parameter	Code	Condition	Remark	
Cha	nnel Sv	witch (Input Mux S								
0x10	16	Select_ Input_1	Select Channel 1	С	0				Select +IN1, -IN1; Channel 1	
0x11	17	Select_ Input_2	Select Channel 2	с	0				Select +IN2, -IN2; Channel 2	
0x12	18	Select_ Input_3	Select Channel 3	С	0				Select +IN3, -IN3; Channel 3	
0x13	19	Select_ Input_4	Select Channel 4	С	0				Select +IN4, -IN4; Channel 4	
0x14	20	Select_ Input_5	Select Channel 5	С	0				Select +IN5, -IN5; Channel 5	
0x15	21	Select_ Input_6	Select Channel 6	С	0		this red	red	Select +IN6, -IN6; Channel 6	
0x16	22	Select_ Input_7	Select Channel 7	С	0	<u> </u>			Select +IN7, -IN7; Channel 7	
0x17	23	Select_ Input_8	Select Channel 8	С	0	net		Channel	Select +IN8, -IN8; Channel 8	
0x18	24	Select_ Input_9	Select Channel 9	С	0	ntil me	N/A	selected	Select +IN9, -IN9; Channel 9	
0x19	25	Select_ Input_10	Select Channel 10	С	0	meing			Select +IN10, -IN10; Channel 10	
0x1A	26	Select_ Input_11	Select Channel 11	С	0				Select +IN11, -IN11; Channel 11	
0x1B	27	Select_ Input_12	Select Channel 12	С	0	d'ng ed			Select +IN12, -IN12; Channel 12	
0x1C	28	Select_ Input_13	Select Channel 13	С	00	o dei			Select +IN13, -IN13; Channel 13	
0x1D	29	Select_ Input_14	Select Channel 14	С	00				Select +IN14, -IN14; Channel 14	
0x1E	30	Select_ Input_15	Select Channel 15	C	000				Select +IN15, -IN15; Channel 15	
0x1F	31	Select_ Input_16	Select Channel		20				Select +IN16, -IN16; Channel 16	
indated in and in a second sec										



# XR10910

Reg No.		Nome	Function	R/	Byte of	Dovomotor	Default	Power-up	Domosti
Hex	Dec	Name	Function	C	Parameter	Parameter	Code	Condition	пепак
Offs	et DAC	Config	-					-	
0x20	32	DAC1	Configures DAC offset applied to Channel 1	R/W	2				
0x21	33	DAC2	Configures DAC offset applied to Channel 2	R/W	2				
0x22	34	DAC3	Configures DAC offset applied to Channel 3	R/W	2				
0x23	35	DAC4	Configures DAC offset applied to Channel 4	R/W	2				
0x24	36	DAC5	Configures DAC offset applied to Channel 5	R/W	2		this	thed	
0x25	37	DAC6	Configures DAC offset applied to Channel 6	R/W	2	6	1,30		
0x26	38	DAC7	Configures DAC offset applied to Channel 7	R/W	2	ationna	tioneanth		
0x27	39	DAC8	Configures DAC offset applied to Channel 8	R/W	2	[10]: DAC Sign	000	0mV	Bit 10 controls the sign of the DAC offset voltage. Bits 9 thru 0 control the value of
0x28	40	DAC9	Configures DAC offset applied to Channel 9	R/W	2	[9:0]CDAC Range	UXUU	offset	[10]: DAC Sign 0 = positive; 1 = negative
0x29	41	DAC10	Configures DAC offset applied to Channel 10	R/W	2	ol on gred			
0x2A	42	DAC11	Configures DAC offset applied to Channel 11	R/W	02	o de			
0x2B	43	DAC12	Configures DAC offset applied to Channel 12	R/W	220	000			
0x2C	44	DAC13	Configures DAC offset applied to Channel 13	B/W	2 2				
0x2D	45	DAC14	Configures DAC offset applied to Channel 14	R/W	2				
0x2E	46	DAC15	Configures DAC offset applied to Channel 15	R/W	2				
0x2F	47	DAC16	Configures DAC offset applied to Channel 16	R/W	2				

#### NOTE:

Register Numbers not listed above have no function.



Table	2.	DAC	Registers
-------	----	-----	-----------

Hex
0x3FF
0x000
0x7FF
0x400

D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0	Offset % of FS Input	Voltage RTI
0	1	1	1	1	1	1	1	1	1	1	50	+560mV
0	0	0	0	0	0	0	0	0	0	0	0	0
1	1	1	1	1	1	1	1	1	1	1	-50	-560mV
1	0 0 0 0 0 0 0 0 0						0	0	0	0	0	
DAC Sian	10-bit DAC Range											



# **Pin Configuration**



NOTE:

MaxLinear recommends grounding the exposed pad.

# **Pin Functions**

Pin No.	Pin Name	Description
1	IN1+	Positive Input 1
2	IN1-	Negative Input 1
3	IN2+	Positive Input 2
4	IN2-	Negative Input 2
5	IN3+	Positive Input 3
6	IN3-	Negative Input 3
7	IN4+	Positive Input
8	IN4-	Negative Input 4
9	IN5+	Positive Input 5
10	IN5-	Negative Input 5
11	IN6+	Positive Input 6
12	IN6-	Negative Input 6
13	IN7+	Positive Input 7
14	IN7-	Negative Input 7
15	IN8+	Positive Input 8
16	IN8-	Negative Input 8
17	IN9+	Positive Input 9
18	IN9-	Negative Input 9
19	IN10+	Positive Input 10
20	IN10-	Negative Input 10

Pin No.	Pin Name	Description			
21	IN11+	Positive Input 11			
22	IN11-	Negative Input 11			
23	IN12+	Positive Input 12			
24	IN12-	Negative Input 12			
25	IN13+	Positive Input 13			
26	IN13-	Negative Input 13			
27	IN14+	Positive Input 14			
28	IN14-	Negative Input 14			
29	IN15+	Positive Input 15			
30	IN15-	Negative Input 15			
31	IN16+	Positive Input 16			
32	IN16-	Negative Input 16			
33	BRDG	BRDG Power Connection ( LDO output )			
34	AGND	Analog Ground			
35	OUT	Output			
36	VCC	Analog Supply			
37	DGND	Digital Ground			
38	SCL	Serial Clock Input			
39	SDA	Serial Data Input/Output			
40	VDD	Digital Supply			



# **Typical Performance Characteristics**

 $T_A = 25^{\circ}C$ ,  $V_{CC} = 3.3V$ ,  $V_{DD} = 1.8V$ ,  $R_L = 10k\Omega$  to 1.5V; G = 760; unless otherwise noted.





# **Typical Performance Characteristics**

 $T_A = 25^{\circ}C$ ,  $V_{CC} = 3.3V$ ,  $V_{DD} = 1.8V$ ,  $R_L = 10k\Omega$  to 1.5V; G = 760; unless otherwise noted.



Figure 14. Input Voltage Noise vs. Frequency

Figure 15. 0.1Hz to 10Hz RTI Voltage Noise



# **Typical Performance Characteristics**

 $T_A = 25^{\circ}C$ ,  $V_{CC} = 3.3V$ ,  $V_{DD} = 1.8V$ ,  $R_L = 10k\Omega$  to 1.5V; G = 760; unless otherwise noted.



# **Functional Block Diagram**



# **Application Information**

The XR10910 sensor interface includes a 16:1 differential multiplexor (mux), a programmable gain instrumentation amplifier, a 10-bit offset correction DAC and an LDO. An I<sup>2</sup>C interface controls the many functions and features of the XR10910. The XR10910 is designed to integrate multiple bridge sensors with an ADC/MCU or FPGA.

Each bridge sensor connected to the XR10910 has its own inherent offset that if not calibrated out can decrease sensitivity and overall performance of the sensor system. The on-board DAC introduces an offset into the instrumentation amplifier to calibrate the offset voltage generated by the sensors. An independent offset can be set for each of the 16 channels. Only the offset voltage of the active channel is applied to the PGA.

The programmable gain instrumentation amplifier offers 8 selectable gains from 2V/V to 760V/V to amplify the signal such that it falls within the input range of the ADC.

An integrated LDO provides a regulated voltage to power the input bridge sensors and is selectable, between 3V and 2.65V. The LDO can be set to turn off when the XR10910 is in Sleep Mode to save power. The XR10910 also provides the ability to monitor the LDO current. When the XR10910 is in Current Sense Mode, an internal 2:1 mux allows a voltage proportional to the LDO current to be present at the output. Once all channels have been calibrated, the LDO current can be used to indirectly monitor any voltage or resistive changes seen by the inputs.

The XR10910 also includes an internal 1.5V reference that is used by the internal LDO circuitry and used to set the reference voltage for the programmable gain instrumentation amplifier.

During sleep mode, the analog components of the XR10910 are powered down for added power savings.

The XR10910 offers many functions, each controlled by the  $I^2C$  compatible serial interface:

- Input Selection
- Gain Selection
- Offset Correction
- LDO Enable / Select
- Current Sense Mode
- Sleep Mode (Analog Power Down)



#### Power Up

After initial system power up, the I<sup>2</sup>C master must provide one SCL clock pulse prior to the first I<sup>2</sup>C access (first start condition). The first access to the XR10910 must be a **RESET** command.



Figure 21: I<sup>2</sup>C Power Up

#### I<sup>2</sup>C Bus Interface

SDA

SCL

The I<sup>2</sup>C-bus interface consists of two lines: serial data (SDA) and serial clock (SCL). The XR10910 works as a slave and supports both standard mode transfer rates (100 kbps) and fast mode transfer rates (400 kbps) as defined in the I<sup>2</sup>C-Bus specification. The I<sup>2</sup>C-bus interface follows all standard I<sup>2</sup>C protocols. Some information is provided below, for additional information, refer to the I<sup>2</sup>C-bus specifications.



After the master detects this acknowledge, the next byte transmitted by the master is the sub-address. This 8-bit sub-address contains the address of the register to access. The XR10910 Register List is shown in Table 1. Depending on the register accessed, there will be up to two additional data bytes transmitted by the master. Refer to the "Byte of Parameter" column in the Register Table. The XR10910 will respond to each write with an acknowledge.

#### **Stop Condition**

To signal the end of the data transfer, the master generates a stop condition by pulling the SDA line from low to high while the SCL line is high, as shown in Figure 22.

Figures 23 and 24 illustrate a write and a read cycle. For complete details, see the I<sup>2</sup>C-bus specifications.



#### I<sup>2</sup>C Bus Addressing

The XR10910 uses a 7-bit address space. For the standard XR10910, the default address is 0x67 (110 0111).

#### Table 4: XR10910 I<sup>2</sup>C Address Map

I <sup>2</sup> C Address	Orderable Part Number
0x67	XR10910IL40TR-F

A read or write transaction is determined by bit-0 of the slave address, (shown as an "x" in Table 4 above). If bit-0 is '0', then it is a write transaction. If bit-0 is '1', then it is a read transaction.

> An I2C sub-address is sent by the I2C master following the slave address. The sub-address contains the XR10910 register address being accessed. Table 1 illustrates the available XR10910 register addresses.

> After the last read or write transaction, the I2C-bus master will set the SCL signal back to its idle state (HIGH).

A start condition

- A slave address cycle
- Zero, one, or two data cycles depending on the XR10910 register accessed

The basic I<sup>2</sup>C access cycle for the XR10910 consists of:

A stop condition

#### Start Condition

The master initiates data transfer by generating a start condition. The start condition is when a high-to-low transition occurs on the SDA line while SCL is high, as shown in Figure 22.

#### **Slave Address Cycle**

After the start condition, the first byte sent by the master is the 7-bit address and the read/write direction bit R/W on the SDA line. If the address matches the XR10910's internal fixed address, the XR10910 will respond with an acknowledge by pulling the SDA line low for one clock cycle while SCL is high.



#### Inputs and Input Selection

The XR10910 includes 16 differential inputs and a 16:1 differential mux that is controlled by an I<sup>2</sup>C compatible 2 wire serial interface. The XR10910 is designed to accept 16 differential inputs.

- If fewer than 16 differential inputs are required, tie the unused inputs to GND.
- If single ended inputs are required, tie the unused inputs to 1.5V.

The input common mode range of the XR10910 is typically 0.6V to 2.4V when running from a 3.3V supply. The XR10910 offers a very wide gain range. In most cases, the output voltage swing will be the limiting factor.

When the XR10910 is powered-up, the default input selected is Channel 1.

Inputs are selected via I<sup>2</sup>C using one of 16 register addresses 0x10 thru 0x1F. Refer to the Register List in Table 1.

Example: The example below illustrates how to select Channel 5.

0 S

#### Gain Selection

The XR10910 offers 8 selectable fixed gains ranging from 2V/V to 760V/V. When the XR10910 is powered-up, the default gain is 2V/V.

The gain is selected via  $I^2C$  using the register address 0x06 followed by another byte of data to select the gain. Refer to the Register List in Table 1 and the Gain Register list in Table 3.

Example: The example below illustrates how to select a gain of 150V/V.

To start communication with the XR10910, repeat steps 1-3 as shown in the inputs and input Selection section on page 16.

6 v 6								
Step 4	7	6	5	4	3	2	1	0
Master sends address of register to access	0	0	0	0	0	1	1	0
left of		regi	<b>G</b> a	ain s add	Sele Iress	e <b>ct</b> s = (	)x06	6
i ell'est								
Step 5	9							
XB10910 sends acknowledge	A							

Since the Gain Select register was accessed, the XR10910 is expecting another byte of data from the master to complete the command. Refer to the "Byte of Parameter" column in the Register List (Table 1). D0 thru D2 are used to select the gain. Refer to the Gain Register list in Table 3, 150V/V is D2 = 1, D1 = 0, and D0 = 0. This translates to a hex code of 0x04, since a full byte of data (8-bits) will be sent.

Step 6	7	6	5	4	3	2	1	0
Master sends gain register data to select G=150	0	0	0	0	0	1	0	0
		Gai	n of	150	V/V	= 0	x04	

Step 7	9
XR10910 sends acknowledge	А

Step 8	0
Master sends stop condition	Р

White Block = host to XR10910, Red Block = XR10910 to host Grey Block = Notes

								0
Step 2	7	6	5	4	3	2	0	0
Master sends XR10910 address with write bit	1	1	0	0	1	2	1	6
		7 Ad	-bit ddre	XR1	1091 = 0x	0 67	<i>b</i>	w
Step 3	9							
XR10910 sends acknowledge	Α	Ç		$\langle \cdot \rangle$				
	9.	5	0					
Step 4	7	6	5	4	3	2	1	0
Master sends address of register to access	0	0	0	1	0	1	0	0
			Sal	aat	Inn	+ 5		

register address = 0x14

Step 5	9
XR10910 sends acknowledge	А

Step 6	0
Master sends stop condition	Ρ

White Block = host to XR10910, Red Block = XR10910 to host Grey Block = Notes



Step 1

Master sends start condition

#### **Offset Correction**

The XR10910 has a 10-bit offset correction DAC that can be used to provide digital calibration on each of the 16 inputs. Only the offset voltage of the active channel is applied to the PGA.

The DAC offset of each channel is controlled by the  $I^2C$  compatible interface. At any time, the master can read or write to any of the DAC offset registers. The DAC offset for each channel is set via  $I^2C$  using the register addresses 0x20 thru 0x2F followed by another two bytes of data to set the polarity and value of the offset voltage. Refer to the Register List in Table 1.

A ±560mV offset correction range is available. The full range of the DAC offset is only available at a gain of 2. At higher gains, the output voltage range of the XR10910 will be exceeded if the full range of the DAC offset is used. The internal 10-bit DAC allows 1,024 different offset voltage settings between 0mV and 560mV. The polarity of the offset correction is set with an additional bit. The unit offset is determined by the following:

Unit offset = 
$$\frac{\text{Total Offset}}{\text{DAC output levels}} = \frac{560\text{mV}}{1024} = 547\mu\text{V}$$

From Table 3:

- 0x00 (hex) or 0 00 0000 0000 (binary) applies a om V offset
- 0x3FF (hex) or 0 11 1111 1111 (binary) applies a +560mV offset
- 0x7FF (hex) or 1 11 1111 1111 (binary) applies a -560mV offset

Each DAC output level provides an additional  $547\mu$ V of offset. To determine what DAC output level corresponds to a specific desired offset, use the following equation:

$$x = \frac{\text{Desired Offset}}{\text{Unit Offset}}$$

See example below for additional information.

Example: The example below illustrates how to set the DAC offset for channel 4 to a value of 75mV.

To start communication with the XR10910, repeat steps 1-3 as shown in the Inputs and Input Selection section on page 16.

Step 4	7	6	5	4	3	2	1	0
Master sends address of register to access	0	0	1	0	0	1	1	0
		DA	<b>C4</b> r	egis – 0	ter a	add	ress	;

Step 5	9
XR10910 sends acknowledge	A

Since a DAC Offset register was accessed, the XR10910 is expecting another two bytes of data from the master to complete the command. Refer to the "Byte of Parameter" column in the Register List (Table 1). D0 thru D9 are used to set the offset voltage and D10 is used to set the sign of the offset voltage, 0 = positive and 1 = negative. Refer to the DAC Offset register list in Table 2.

To determine what DAC output level corresponds to 75mV, use the following equation:

DAC Output Level = 
$$\frac{\text{Desired Offset}}{\text{Unit Offset}} = \frac{75\text{mV}}{547\mu\text{V}} = 137$$

A decimal value of 137 corresponds to 75mV. Therefore:

0x89 (hex) or 0 00 1000 1001 (binary) applies a +75mV offset

• 0x489 (hex) or 1 00 1000 1001 (binary) applies a -75mV Coffset

1	Step 6	15	14	13	12	11	10	9	8
	Master sends 1 <sup>st</sup> byte of DAC offset register data to select an offset of +75mV	0	0	0	0	0	0	0	0
							Sign	2 MSBs of <sup>2</sup> output level sponds to 1	10-bit DAC that corre- 37 (0x89)

Step 7	9
XR10910 sends acknowledge	А

Step 8	7	6	5	4	3	2	1	0
Master sends 2 <sup>nd</sup> byte of DAC offset register data to select an offset of +75mV	1	0	0	0	1	0	0	1
	8 lev	LSB /el tl	s of nat c	10-l orre (0x	oit D espo 89)	AC nds	outp to 1	ut 37

Step 9	9
XR10910 sends acknowledge	А

Step 10	0
Master sends stop condition	Ρ

White Block = host to XR10910, Red Block = XR10910 to host Grey Block = Notes



#### LDO Enable / Select (Power to External Bridge Sensors)

The XR10910 includes an on-board LDO that provides a regulated voltage that can be used to power external input bridge sensors. Two voltage options are available, 3V and 2.65V. The LDO voltage is selected via the I<sup>2</sup>C compatible two-wire serial interface.

When the XR10910 is powered-up, the default LDO voltage is 3V.

When the XR10910 is active (not in sleep mode), the LDO is always on. If the LDO voltage is not used, the LDO output can be left floating. The LDO can either stay on or shut down while the XR10910 is in Sleep Mode.

- Set LDO to shut down while XR10910 is in Sleep Mode to save power
- Set LDO to stay on while XR10910 is in Sleep Mode to improve wake-up time

The LDO voltage and disable setting are selected via I<sup>2</sup>C using the register address 0x07 followed by another byte of data to select the voltage and disable setting. Refer to the Register List in Table 1 and the example below for more information.

Example: The example below illustrates how to select an LDO voltage of 2.65V and keep the LDO enabled during Sleep Mode.

To start communication with the XR10910, repeat steps 1-3 as shown in the Inputs and Input Selection section of page 11.

			V.	- <b>X</b>		- X.		
Step 4	7	6	5	4	3	2	1	0
Master sends address of register to access	0	0	0	0	0	1	1	1
The	22	egi:	LD ster	add	ettii Ires:	n <b>gs</b> s = (	0x07	7
Step 5	9							
XR10910 sends acknowledge	Α							

Since the LDO Settings register was accessed, the XR10910 is expecting another byte of data from the master to complete the command. Refer to the "Byte of Parameter" column in the Register List (Table 1). D0 and D1 are used to select the LDO voltage and enable/disable the LDO during Sleep Mode. Bit 0 (D0) controls the LDO voltage (0: 3V; 1: 2.65V). Bit 1 (D1) is only applicable in Sleep Mode. Bit 1 controls whether the LDO shuts down or stays on during sleep mode (0: Enable; 1: Disable). When the XR0910 is active, the LDO is always on.

Step 6	7	6	5	4	3	2	1	0
Master sends code to select LDO voltage of 2.65V and Enable LDO during Sleep Mode	0	0	0	0	0	0	0	0
							0 = Enable	1 = 2.65V

Step 7	9
XR10910 sends acknowledge	А

Step 8 🥠 👌	0
Master sends stop condition	Р

White Block = host to XR10910, Red Block = XR10910 to host Grey Block = Notes

# Current Sense Mode (Monitoring the LDO Current)

Current Sense Mode is activated via  $I^2C$  using the register address 0x08. When activated, the LDO current is sensed and a proportional voltage is present at the output of the XR10910 (ILDO = VOUT/RL). Current Sense Mode stays active until the XR10910 receives any input select command (0x10 thru 0x1F).

Current sense mode can be used to monitor the change over time of the bridge impedance.

#### Sleep Mode (Analog Power Down)

Sleep Mode is activated via I<sup>2</sup>C using the register address 0x05. When activated, the XR10910 will enter Sleep Mode. During Sleep Mode, the analog portion of the XR10910 is disabled. All register settings are retained during Sleep Mode.

During Sleep Mode, the nominal supply current will drop below  $70\mu A$  (with LDO on) and below  $45\mu A$  (with LDO off).

During Sleep Mode, the master can read the value in any register that saves a value during sleep mode. The only I<sup>2</sup>C commands that can be received or processed is the SLEEP\_OUT (wake up) command (0x04) or the LDO on/off and voltage command (0x07). All other register addresses will be ignored.

Register address 0x04 is used to return to normal operation (exit Sleep Mode).

By default, the XR10910 is active.



#### Typical Application - 16:1 Bridge Sensor Interface

The XR10910 was designed to interface multiple bridge sensors with a microcontroller or FPGA as illustrated in Figure 25.

The bridge output signal is differential (Vo+ and Vo-). Ideally, the unloaded bridge output is zero (Vo+ and Vo- are identical). However, in-exact resistive values result in a difference between Vo+ and Vo-. This bridge offset voltage can be substantial and vary between sensors. The XR10910 provides the ability to calibrate the bridge offset on each of the 16 bridge sensors using the on-board DAC.



#### Layout Considerations

General layout and supply bypassing play major roles in high frequency performance. Follow the steps below as a basis for high frequency layout:

- Include 6.8µF and 0.1µF ceramic capacitors for power supply decoupling
- Place the 6.8µF capacitor within 0.75 inches of the power pin
- Place the 0.1µF capacitor within 0.1 inches of the power pin
- Connection to the exposed pad is not required. Exposed pad can be connected to ground (GND).
- Minimize all trace lengths to reduce series inductances

### **Mechanical Dimensions**

#### QFN-40 Package



#### TERMINAL DETAILS

- ALL DIMENSIONS ARE IN MILLIMETERS, ANGLES ARE IN DEGREES.
- DIMENSIONS AND TOLERANCE PER JEDEC MO-220.

Drawing No.: POD-00000041

Revision: B.3



## **Recommended Land Pattern and Stencil**

### QFN-40 Package



Drawing No.: POD-00000041 Revision: B.3



# Ordering Information<sup>(1)</sup>

Part Number	Operating Temperature Range	Lead-Free	Package	Packaging Method	
XR10910IL40-F	10°C to 195°C	<b>V</b> an <sup>(2)</sup>	OEN 40	Tray	
XR10910IL40TR-F	-40 C 10 +85 C	fes	QFN-40	Tape & Reel	
XR10910IL40EVB Evaluation Board					

NOTES:

1. Refer to <u>www.exar.com/XR10910</u> for most up-to-date Ordering Information.

2. Visit <u>www.exar.com</u> for additional information on Environmental Rating.

# **Revision History**

Part	Part	Part N A
1A	May 2015	Initial Release
1B	July 2015	Added Typical Performance Characteristics section.
1C	May 2016	Updated to latest format and added figure numbers. Updated Figures 1 and 25. Added Figure 2. Updated page number reference in Gain section of Electrical Characteristics table. Updated Figure 24. Added clarity to I <sup>2</sup> C Bus Addressing section. Updated Table 4. Updated Step 2 in Inputs and Input Selection section.
1D	March 2018	Updated to MaxLinear lego Updated format and Ordering information table. Added I <sup>2</sup> C Power Up section.
1E	January 2019	Correct typo in Recommended Stencil.

nis e





**Corporate Headquarters:** 5966 La Place Court Suite 100 Carlsbad, CA 92008 Tel.:+1 (760) 692-0711 Fax: +1 (760) 444-8598 www.maxlinear.com

The content of this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by MaxLinear, Inc.. MaxLinear, Inc. assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide. Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced into, stored into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopyrig, ecording, or otherwise), or for any purpose, without the express written permission of MaxLinear, Inc.

Maxlinear, Inc. does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of the life support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications unless MaxLinear, Inc. receives, in writing, assurances to its satisfaction that: (a) the risk of injury or damage has been minimized; (b) the user assumes all such risks; (c) potential liability of MaxLinear, Inc. is adequately protected under the circumstances.

MaxLinear, Inc. may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from MaxLinear, Inc., the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property.

Company and product names may be registered trademarks or trademarks of the respective owners with which they are associated

© 2016 - 2019 MaxLinear, Inc. All rights reserved